



KING Portable Cabling Winches

KING Models KN500 and KN1000

- 500kg and 1000kg capacity available
- One man operation
- High manoeuvrability
- Fully portable
- Compact and lightweight
- Excellent work performance
- Proven versatility
- Available ex-stock

SPECIFICATION

	KN500	KN1000
• SPEC NO.:	30143686-5	30143683-5
• ENGINE:	8HP Petrol (hand start)	12HP Petrol (hand start)
• GEARBOX:	Wormdrive	Wormdrive
• CLUTCH:	(Drive type) tensioned belt with load creep brake	
• SPEED CONTROL:	By engine throttle control ONLY	
• CLUTCH (Pull Back):	Enclosed sprag clutch	
• TAILING REEL:		
Diameter	480mm	480mm
Width	210/225mm	210/225mm
Core	145mm	145mm
Mtg. hole	33mm	33mm
• DRAW ROPE:		
Diameter max	8mm	8mm
Diameter min	5mm	5mm
Length self tailed	1100m (5mm dia)	1100m (5mm dia)
Length hand tailed	No limit	No limit
• PERFORMANCE:		
Line tension (approx)	500kg	1000kg
Line speed (unladen)	40m/min	27m/min
• TRANSIT CUBE:	0.383m ³	0.408m ³
• MACHINE WEIGHT:	86kg	104kg