

SAHLINS 902 POWERED REELER

Specification

Engine:	Air-cooled 4-stroke, 2 Cyl 18Hp electric start.
Pulling Force:	Max 3000kg on 250mm drum dia.
Pulling Speed:	Infinitely variable 0-100mm/min.
Hydraulic:	Pump with variable displacement. Max oil pressure 210 bar, max flow rate 60Ltr/min.
Anchoring:	Two hydraulically operated stabiliser legs.
Maximum drum dimensions:	Max diam 1800mm, max width 1050mm.
Safety:	Fail safe brake hold at stop.
Overall Dimensions (loaded):	Length: 3200mm Width: 2350mm Height: 1500mm
Weight:	800kg



The Rotrex line machine is a hydraulically powered drum winch. It has variable pulling force and reel speed control. The machine is fitted with a negative action brake, which automatically applies when drum movement is stopped. It is equipped with independent hydraulic legs to either side of the machine, which allows full levelling to be carried out. The jockey wheel at the towing end of the machine is both adjustable and robust in design. The machine is built with road suspension and is fitted with both over-run and parking brakes.



All controls are concentrated on the left side of the machine. Indicator (dynamometer) for pulling force is located under new hydraulic controls.



The power comes from petrol driven hydraulic power pack, with built-in cooling fan to guarantee safe and long working time.