

	APPLICATION	POWER SOURCE	POWER SOURCE	LINE PULL	LINE SPEED	DRUM STORAGE	WINCH CONTROL	WINCH FASTENING	WEIGHT
FA2I	Lifting	Air	6.3 bar (90psi) @8m ³ /min	2,000kg	0-17m/min	298m x 13mm	Control lever on winch	Bolted or welded via deck plates	386kg
FA2.5I	Lifting	Air	6.3 bar (90psi) @20m ³ /min	2,270kg	0-40m/min	203m x 16mm	Control lever on winch	Bolted or welded via deck plates	481kg
FA5I	Lifting	Air	6.3 bar (90 psi) @ 19.9m ³ /min (700 cfm)	5,000kg	0-16m/min	347m x 19mm, 254m x 22mm	Control lever on winch	Bolted or welded via deck plates	900kg
FA5A	Lifting	Air	6.3 bar (90 psi) @ 20.0m ³ /min (700 cfm)	4,545kg	0-13m/min	486m x 16mm, 366m x 19mm	Control lever on winch	Bolted or welded via deck plates	569kg
FA7I	Lifting	Air	6.3 bar (90psi) @21m ³ /min	7,000kg	0-12m/min	268m x 22mm	Control lever on winch	Bolted or welded via deck plates	1000kg
FA10I	Lifting	Air	6.3 bar (90 psi) @ 22.7m ³ /min (800 cfm)	10,000kg	0-7m/min	405m x 25mm, 313m x 29mm	Control lever on winch	Bolted or welded via deck plates	1451kg