

AIR WINCHES – LIFTSTAR RANGE

	APPLICATION	POWER SOURCE	POWER SOURCE	LINE PULL	LINE SPEED	DRUM STORAGE	WINCH CONTROL	WINCH FASTENING	WEIGHT
LIFTSTAR 300	Lifting	Air	6.3 bar (90 psi) @ 2.2m ³ /min (77 cfm)	300kg	0-40m/min	307m x 5mm	Control lever on winch	Bolted or welded via deck plates	49kg
LIFTSTAR 600	Lifting	Air	6.3 bar (90 psi) @ 2.2m ³ /min (77 cfm)	600kg	0-30m/min	60m x 6.5mm	Control lever on winch	Bolted or welded via deck plates	28kg
LIFTSTAR 1500	Lifting	Air	6.3 bar (90 psi) @ 3.5m ³ /min (125 cfm)	1,500kg	0-20m/min	32m x 10mm	Control lever on winch	Bolted or welded via deck plates	63.5kg
LIFTSTAR 2000	Lifting	Air	7 bar (100 psi) @ 10m ³ /min (350 cfm)	2,000kg	0-50m/min	103m x 13mm	Control lever on winch	Bolted or welded via deck plates	230kg
LIFTSTAR 5000	Lifting	Air	7 bar (100 psi) @ 10m ³ /min (350 cfm)	5,000kg	0-10m/min	473m x 19mm	Control lever on winch	Bolted or welded via deck plates	760kg



LIFTSTAR 600



LIFTSTAR 2000



LIFTSTAR 5000